<u>MATERIAL SAFETY DATA SHEET</u>

ODOR LESS WHITE S/G BASES/COLORS

Page:

PRODUCT NAME: ODOR LESS WHITE S/G BASES/COLORS

PRODUCT CODE: OF-260

HMIS CODES: H F R P

MANUFACTURER'S NAME: LANCO MFG. CORP.

ADDRESS

: URB. APONTE #5

SAN LORENZO, PUERTO RICO

00754

EMERGENCY PHONE

: (787) 736-4200

DATE PRINTED

: 01/21/04

INFORMATION PHONE : (787) 736-4200

NAME OF PREPARER : LANCO MFG. CORP.

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

REPORTABLE COMPONENTS CAS NUMBER

VAPOR PRESSURE

WEIGHT

on Hy & TEMP

PERCENT

WATER

* 3-iodo-2-propynyl butyl carbamate

7732-18-5 MIXTURE:

9.2

Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

========= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING RANGE: n/a

VAPOR DENSITY: LIGHTER THAN AIR

COATING V.O.C.: 0.23 1b/q1

SOLUBILITY IN WATER: AQUEOUS SYSTEM

APPEARANCE AND ODOR: SLOW ODOR

SPECIFIC GRAVITY (H20=1): 1.27

EVAPORATION RATE: UNKNOWN

MATERIAL V.O.C.: 0.08 16/g1

FLASH POINT: NONE

METHOD USED: n/a

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a

UPPER: n/a

EXTINGUISHING MEDIA: CO2, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOGNOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD- UP, CLOSED CONTAINERS EXPOSED TO EXTREME REAT MAY EXPLODE DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCT MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE INMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

STABILITY: STABLE CONDITIONS TO AVOID

NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZAROOUS FUMES WHEN HEATED TO DECOMPOSITION, FUMES MAY CONTAIN CARBONNONOXIDE, CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

MATERIAL SAFETY DATA SHEET

ODOR LESS WHITE S/G BASES/COLORS

Page:

2

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INSESTED, CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING AND CONTACT A PHYSICIAN OR YOUR NEAREST POISON CONTROL CENTER. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LINES.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACCIDINGE WITH SAFE HANOLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: REMOVED TO FRESH AIR. IF IN EYES:IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF OF SKIN: REMOVE WITH SOAP AND WATER. REMOVE SUILED CLOTHING. INSESTION: INDUCE VOMITING PROMPTLY ACCORDING TO PHYSICIANS INSESTICATIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

======= SECTION VII -	PRECAUTIONS FOR SAFI	E HANDLING AND	USE ========
-----------------------	----------------------	----------------	--------------

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER, BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFOMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA FORM. CONTAIN SPILLED MATERIAL AND REMOVED WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 1888 F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINER, KEEP DUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

MINE

SECTION VIII - CONTROL MEASURES ==============

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS, SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDINGOR GRINDING OPERATION, USE NICSH/MSHA APROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARDS IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED.

EYE PROTECTION

	je: 3
O NOT GET IN EYES. SAFETY EYEMEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT OT REQUIRED.	
JORK/HYGIENIC PRACTICES EMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE BATHROOM.	
======================================	
PROPER SHIPPING NAME OT REGULATED	
IAZARD CLASS /A	
N NUMBER 'A	

The information contained herein is based on data believed by this company to be accurate, but we do not assume any liability for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsability of the user.

PACKING GROUP

N/A